



GARLOCK BEARINGS LTD



1.575 Inch | 40 Millimeter x 3.15 Inch | 80
Millimeter x 1.189 Inch | 30.2 Millimeter SKF 3208
A-Z/C3 Angular Contact Ball Bearings

Bearing No. 3208 A-Z/C3

3208 A-Z/C3 Bearing 2D drawings and 3D CAD models

Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.601
Product Group	B00152
Enclosure	1 Metal Shield
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Double Row
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Steel
Contact Angle	30 Degree
Internal Clearance	C3-Loose
Number of Bearings	1 (Single)
Inch - Metric	Metric
Long Description	40MM Bore; 80MM Outside Diameter; 30.2MM Width; 1 Metal Shield; No Flush Ground; Ball Bearing; Double Row of Balls; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; C3-Loose;



GARLOCK BEARINGS LTD

	Steel Cage; 30 Degree; 1 (
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	3208 A-Z/C3
Weight / LBS	1.3227
d	1.575 Inch 40 Millimeter
D	3.15 Inch 80 Millimeter
B	1.189 Inch 30.2 Millimeter
bore diameter:	40 mm
radial static load capacity:	34 kN
outside diameter:	80 mm
cage material:	Metal
overall width:	1.1875 in
outer ring width:	30.2 mm
contact angle:	30 °
maximum rpm:	8000 RPM
row type & fill slot:	Double-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C3
precision rating:	Not Rated
closure type:	Single Shield
fillet radius:	1 mm
radial dynamic load capacity:	47.5 kN
series:	32