



GARLOCK BEARINGS LTD



2.362 Inch | 60 Millimeter x 4.331 Inch | 110
 Millimeter x 1.437 Inch | 36.5 Millimeter SKF 3212
 A-2RS1/C3 Angular Contact Ball Bearings

Bearing No. 3212 A-2RS1/C3

3212 A-2RS1/C3 Bearing 2D drawings and 3D CAD models

| | |
|---------------------------------|---|
| Category | Angular Contact Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 1.321 |
| EAN | 7316573931270 |
| Product Group | B00152 |
| Enclosure | 2 Seals |
| Flush Ground | No |
| Rolling Element | Ball Bearing |
| Number of Rows of Balls | Double Row |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Snap Ring | No |
| Cage Material | Steel |
| Contact Angle | 30 Degree |
| Internal Clearance | C3-Loose |
| Number of Bearings | 1 (Single) |
| Inch - Metric | Metric |
| Long Description | 60MM Bore; 110MM Outside Diameter; 36.5MM Width; 2 Seals; No Flush Ground; Ball Bearing; Double Row of Balls; ABEC 1 ISO P0; No Filling Slot; |



GARLOCK BEARINGS LTD

| | |
|----------------------------------|--|
| | No Snap Ring; C3-Loose; Steel Cage; 30 Degree; 1 (Single |
| Other Features | NBR Contact Seal |
| Category | Angular Contact Ball Bearing |
| UNSPSC | 31171531 |
| Harmonized Tariff Code | 8482.10.50.28 |
| Noun | Bearing |
| Keyword String | Angular Contact |
| Manufacturer URL | http://www.skf.com |
| Manufacturer Item Number | 3212 A-2RS1/C3 |
| Weight / LBS | 2.8417 |
| B | 1.437 Inch 36.5 Millimeter |
| D | 4.331 Inch 110 Millimeter |
| d | 2.362 Inch 60 Millimeter |
| bore diameter: | 60 mm |
| operating temperature range: | -40 to +210 ° F |
| outside diameter: | 110 mm |
| outer ring width: | 36.5 mm |
| overall width: | 1.4375 in |
| maximum rpm: | 4000 RPM |
| row type & fill slot: | Double-Row Non-Fill Slot |
| finish/coating: | Uncoated |
| internal clearance: | C3 |
| precision rating: | Not Rated |
| closure type: | Double Seal |
| fillet radius: | 1.5 mm |
| radial dynamic load capacity: | 73.5 kN |
| series: | 32 |
| radial static load capacity: | 58-1/2 kN |