



GARLOCK BEARINGS LTD



3205 A-2RS1TN9/MT33 Bearing 2D drawings and 3D CAD models

25 mm x 52 mm x 20.6 mm SKF 3205 A-2RS1TN9/MT33 Angular Contact Ball Bearings

Bearing No. 3205 A-2RS1TN9/MT33

Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.185
EAN	7316570684759
Product Group	B00152
Enclosure	2 Seals
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Double Row
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Polyamide
Contact Angle	30 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Inch - Metric	Metric
Long Description	25MM Bore; 52MM Outside Diameter; 20.6MM Width; 2 Seals; No Flush Ground; Ball Bearing; Double Row of Balls; ABEC 1 ISO P0; No Filling Slot; No Snap Ring;



GARLOCK BEARINGS LTD

	C0-Medium; Polyamide Cage; 30 Degree; 1 (Si
Other Features	NBR Contact Seal Glass Fibre Reinforced Cage MT33-Lithium Soap Thickener Grease
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	3205 A-2RS1TN9/MT33
Weight / LBS	0.4023
B	0.811 Inch 20.6 Millimeter
d	0.984 Inch 25 Millimeter
D	2.047 Inch 52 Millimeter
bore diameter:	25 mm
operating temperature range:	-40 to +210 ° F
outside diameter:	52 mm
cage material:	Fiberglass Reinforced Nylon
overall width:	0.8125 in
outer ring width:	20.6 mm
contact angle:	30 °
maximum rpm:	8500 RPM
row type & fill slot:	Double-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C0
precision rating:	Not Rated
closure type:	Double Seal
fillet radius:	1 mm
radial dynamic load	21.6 kN



GARLOCK BEARINGS LTD

capacity:	
series:	32
radial static load capacity:	14.3 kN
d	25 mm
D	52 mm
B	20.6 mm
d ₂	32.7 mm
D ₂	45.9 mm
r _{1,2} min.	1 mm
a	30 mm
d _a min.	30.6 mm
d _a max.	32.5 mm
D _a max.	46.4 mm
r _a max.	1 mm
Basic dynamic load rating C	21.6 kN
Basic static load rating C ₀	14.3 kN
Fatigue load limit P _u	0.6 kN
Limiting speed	8500 r/min
Calculation factor k _r	0.06
Calculation factor e	0.8
Calculation factor X	0.63
Calculation factor Y ₀	0.66
Calculation factor Y ₁	0.78
Calculation factor Y ₂	1.24
Mass bearing	0.18 kg