



GARLOCK BEARINGS LTD



5.906 Inch | 150 Millimeter x 10.63 Inch | 270 Millimeter x 2.874 Inch | 73 Millimeter SKF NJ 2230 ECM/C3 Cylindrical Roller Bearings

Bearing No. NJ 2230 ECM/C3

NJ 2230 ECM/C3 Bearing 2D drawings and 3D CAD models

Category	Cylindrical Roller Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	19.27
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring - One Side
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes
Inch - Metric	Metric
Other Features	High Capacity 1 Rib Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
Long Description	150MM Bore; Straight Bore Profile; 270MM Outside Diameter; 73MM Width; Brass Cage Material; RBEC 1 ISO P0; Single Row;



GARLOCK BEARINGS LTD

	Inner Ring - One Side Separable; No Snap Ring; Relubricatable; C3-Loose Intern
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	NJ 2230 ECM/C3
Weight / LBS	42.446
B	2.874 Inch 73 Millimeter
d	5.906 Inch 150 Millimeter
D	10.63 Inch 270 Millimeter
bore diameter:	150 mm
static load capacity:	930 kN
outside diameter:	270 mm
precision rating:	Not Rated
overall width:	73 mm
maximum rpm:	2800 RPM
flanges:	(2) Outer Ring, (1) Inner Ring
bearing material:	Steel
bore type:	Straight
cage material:	Brass
number of rows:	1
finish/coating:	Uncoated
internal clearance:	C3
closure type:	Open
ring separation:	Separable Ring
outer ring width:	73 mm
operating temperature range:	Maximum of +300 ° F
fillet radius:	2.5 mm



GARLOCK BEARINGS LTD

dynamic load capacity:	735 kN
series:	NJ22