



GARLOCK BEARINGS LTD



6308LLUC3/EM Bearing 2D drawings and 3D CAD models

NTN 6308LLUC3/EM Single Row Ball Bearings

Bearing No. 6308LLUC3/EM

Category	Single Row Ball Bearings
Inventory	9.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight	0.637
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C3-Loose
Inch - Metric	Metric
Long Description	40MM Bore; 90MM Outside Diameter; 23MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing



GARLOCK BEARINGS LTD

Keyword String	Ball
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	6308LLUC3/5C
Weight / LBS	1.4
d	1.575 Inch 40 Millimeter
Outer Race Width	0.906 Inch 23 Millimeter
D	3.543 Inch 90 Millimeter
bore diameter:	40 mm
precision rating:	ISO Class 0
outside diameter:	90 mm
finish/coating:	Uncoated
overall width:	23 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Sealed
inner ring width:	23 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	23 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	5300 rpm
internal clearance:	C3
fillet radius:	1.5 mm
operating temperature range:	-40 to 120 ° C
maximum rpm:	9200 RPM
dynamic load capacity:	40500 N
series:	63
static load capacity:	24000 N
manufacturer product page:	Click here