



GARLOCK BEARINGS LTD



71807 ACD/HCP4 Bearing 2D drawings and 3D CAD models

71807 ACD/HCP4 SKF High Speed Angular Contact Ball Bearings

Bearing No. 71807 ACD/HCP4

Size	47x35x7 mm
Bore Diameter	47 mm
Outer Diameter	35 mm
Width	7 mm
d	35 mm
D	47 mm
B	7 mm
d ₁	39.1 mm
d ₂	39.1 mm
D ₁	43.1 mm
r _{1,2} - min.	0.3 mm
r _{3,4} - min.	0.15 mm
a	13.1 mm
d _a - min.	37 mm
d _b - min.	37 mm
D _a - max.	45 mm
D _b - max.	46.2 mm
r _a - max.	0.3 mm
r _b - max.	0.15 mm
d _n	39.5 mm
Basic dynamic load rating - C	4.4 kN
Basic static load rating - C ₀	4 kN
Fatigue load limit - P _u	0.173 kN
Limiting speed for grease	30000 r/min



GARLOCK BEARINGS LTD

Lubrication	
Limiting speed for oil lubrication	48000 mm/min
Ball - D_w	3.175 mm
Ball - z	26
G_{ref}	0.28 cm ³
Calculation factor - e	0.68
Calculation factor - Y_2	0.87
Calculation factor - Y_0	0.38
Calculation factor - X_2	0.41
Calculation factor - Y_1	0.92
Calculation factor - Y_2	1.41
Calculation factor - Y_0	0.76
Calculation factor - X_2	0.67
Preload class A - G_A	39 N
Preload class B - G_B	115 N
Preload class C - G_C	230 N
Calculation factor - f	1.18
Calculation factor - f_1	0.97
Calculation factor - f_{2A}	1
Calculation factor - f_{2B}	1.09
Calculation factor - f_{2C}	1.17
Calculation factor - f_{HC}	1.02
Preload class A	85 N/micron
Preload class B	132 N/micron
Preload class C	179 N/micron
d_1	39.1 mm
d_2	39.1 mm
D_1	43.1 mm
$r_{1,2}$ min.	0.3 mm



GARLOCK BEARINGS LTD

$r_{3,4}$ min.	0.15 mm
d_a min.	37 mm
d_b min.	37 mm
D_a max.	45 mm
D_b max.	46.2 mm
r_a max.	0.3 mm
r_b max.	0.15 mm
d_n	39.5 mm
Basic dynamic load rating C	4.36 kN
Basic static load rating C_0	4.05 kN
Fatigue load limit P_u	0.173 kN
Attainable speed for grease lubrication	30000 r/min
Attainable speed for oil-air lubrication	48000 r/min
Ball diameter D_w	3.175 mm
Number of balls z	26
Reference grease quantity G_{ref}	0.28 cm ³
Preload class A G_A	39 N
Static axial stiffness, preload class A	85 N/ μ m
Preload class B G_B	115 N
Static axial stiffness, preload class B	132 N/ μ m
Preload class C G_C	230 N
Static axial stiffness, preload class C	179 N/ μ m
Calculation factor f	1.18
Calculation factor f_1	0.97
Calculation factor f_{2A}	1
Calculation factor f_{2B}	1.09
Calculation factor f_{2C}	1.17
Calculation factor f_{HC}	1.02



GARLOCK BEARINGS LTD

Calculation factor e	0.68
Calculation factor (single, tandem) Y_2	0.87
Calculation factor (single, tandem) Y_0	0.38
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back-to-back, face-to-face) Y_1	0.92
Calculation factor (back-to-back, face-to-face) Y_2	1.41
Calculation factor (back-to-back, face-to-face) Y_0	0.76
Calculation factor (back-to-back, face-to-face) X_2	0.67
Mass bearing	0.026 kg