



GARLOCK BEARINGS LTD



S7208 ACD/P4A Bearing 2D drawings and 3D CAD models

S7208 ACD/P4A SKF High Speed Angular Contact Ball Bearings

Bearing No. S7208 ACD/P4A

Size	80x40x18 mm
Bore Diameter	80 mm
Outer Diameter	40 mm
Width	18 mm
d	40 mm
D	80 mm
B	18 mm
d ₁	53.3 mm
d ₂	53.3 mm
D ₂	69.7 mm
r _{1,2} - min.	1.1 mm
r _{3,4} - min.	0.6 mm
a	23.1 mm
d _a - min.	47 mm
d _a - max.	52.5 mm
d _b - min.	47 mm
d _b - max.	52.5 mm
D _a - max.	73 mm
D _b - max.	75.8 mm
r _a - max.	1 mm
r _b - max.	0.6 mm
Basic dynamic load rating - C	31.9 kN
Basic static load rating - C ₀	22.8 kN
Fatigue load limit - P _u	0.98 kN



GARLOCK BEARINGS LTD

Limiting speed for grease lubrication	16000 r/min
Ball - D_w	11.112 mm
Ball - z	14
Calculation factor - e	0.68
Calculation factor - Y_2	0.87
Calculation factor - Y_0	0.38
Calculation factor - X_2	0.41
Calculation factor - Y_1	0.92
Calculation factor - Y_2	1.41
Calculation factor - Y_0	0.76
Calculation factor - X_2	0.67
Preload class A - G_A	200 N
Preload class B - G_B	400 N
Preload class C - G_C	800 N
Preload class D - G_D	1600 N
Calculation factor - f	1.05
Calculation factor - f_1	0.99
Calculation factor - f_{2A}	1
Calculation factor - f_{2B}	1.01
Calculation factor - f_{2C}	1.02
Calculation factor - f_{2D}	1.05
Calculation factor - f_{HC}	1
Preload class A	127 N/micron
Preload class B	165 N/micron
Preload class C	218 N/micron
Preload class D	294 N/micron
d_1	53.3 mm
d_2	53.3 mm
D_2	69.7 mm



GARLOCK BEARINGS LTD

$r_{1,2}$ min.	1.1 mm
$r_{3,4}$ min.	0.6 mm
d_a min.	47 mm
d_a max.	52.5 mm
d_b min.	47 mm
d_b max.	52.5 mm
D_a max.	73 mm
D_b max.	75.8 mm
r_a max.	1 mm
r_b max.	0.6 mm
Basic dynamic load rating C	31.9 kN
Basic static load rating C_0	22.8 kN
Fatigue load limit P_u	0.98 kN
Attainable speed for grease lubrication	16000 r/min
Ball diameter D_w	11.112 mm
Number of balls z	14
Preload class A G_A	200 N
Static axial stiffness, preload class A	127 N/ μ m
Preload class B G_B	400 N
Static axial stiffness, preload class B	165 N/ μ m
Preload class C G_C	800 N
Static axial stiffness, preload class C	218 N/ μ m
Preload class D G_D	1600 N
Static axial stiffness, preload class D	294 N/ μ m
Calculation factor f	1.05
Calculation factor f_1	0.99
Calculation factor f_{2A}	1
Calculation factor f_{2B}	1.01
Calculation factor f_{2C}	1.02



GARLOCK BEARINGS LTD

Calculation factor f_{2D}	1.05
Calculation factor f_{HC}	1
Calculation factor e	0.68
Calculation factor (single, tandem) Y_2	0.87
Calculation factor (single, tandem) Y_0	0.38
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back-to-back, face-to-face) Y_1	0.92
Calculation factor (back-to-back, face-to-face) Y_2	1.41
Calculation factor (back-to-back, face-to-face) Y_0	0.76
Calculation factor (back-to-back, face-to-face) X_2	0.67
Mass bearing	0.38 kg